

# FARGO® DTC4500e

## Direct-to-card Printer

The HID FARGO DTC4500e ID card printer is ideal for organizations requiring robust, high-volume printing every day. Standard features include high-capacity ribbon consumables and dual input card hoppers that allow for maximum card input capacity and the convenient management of multiple card types.



Designed for medium-to-large businesses, schools and local governments seeking high-volume, direct-to-card printing, the DTC4500e offers a powerful and reliable print engine that delivers on both speed and performance. Dual input hoppers and support for high-capacity ribbons enable the DTC4500e to print twice as many full-color cards than most comparable printers before consumables would require replenishing – keeping productivity high and operator maintenance low.

For improved card durability and security, the DTC4500e can be optionally equipped with a dual-sided lamination module that supports increased throughput via the unit's ability to laminate both sides of the card simultaneously.

### Outstanding performance

The DTC4500e also boasts features that enhance the security of your overall card issuance program.

Optional locking hoppers and user-defined passwords lock down printer access ensuring that unauthorized personnel cannot use the printer to print fraudulent cards or steal personal information, while AES-256 data encryption protects cardholder data while in transit, thus guaranteeing data integrity and authentication between PC and printer.

To further safeguard credentials, users can apply standard or custom holographic overlaminates and/or leverage the printer's fluorescent panel printing – allowing issuers to include additional layers of card security as needs dictate.

### Efficient energy consumption

Beyond its comprehensive feature set, the DTC4500e can also play a pivotal role in your green initiatives. GreenCircle® Certified for its efficient energy consumption, the DTC4500e was found to provide a 39 percent energy savings over comparable printers. What's more, the DTC4500's eco-friendly rewrite support allows card text to be erased and reprinted making it ideal for any organization that routinely issues temporary-use cards such as contractor or visitor badges.

Powerful, secure, versatile and eco-friendly, the DTC4500e is an ideal solution for organizations seeking to print superior-quality cards and IDs in higher volumes.

## Key features

- High-quality output – Create high- quality, visually rich credentials
- on demand
- Simple plug-and-play – Leverage an intuitive user-focused interface for easy setup, consumables loading
- and operation
- Built-in security – Enjoy peace of mind with AES-256 encryption and resin scramble data protection
- Earth-friendly – Support your green initiatives with GreenCircle Certified energy efficiency and support for eco-friendly (ECO) refill ribbons and rewritable cards

## Optional features

- Dual-sided printing
- Single-sided or dual-sided lamination
- Contact, contactless and mag stripe encoding
- Ethernet with internal print server
- Locking hoppers
- Same-side input/output

## Additional product features

- FARGO Workbench™ printer maintenance and diagnostic software utility with inclusive Colour Assist spot colour matching
- Support for eco-friendly, refillable (ECO ribbons) and rewritable cards
- Interoperable with Asure ID® card personalization software for card/badge design, database management and technology card encoding

## Encoding options

(Supported smart card and magnetic stripe technologies):

- 125kHz (HID Prox™) reader
- 13.56 MHz (iCLASS® Standard/SE/SR/Seos®, MIFARE Classic®, MIFARE Plus®, MIFARE DESFire®, MIFARE DESFire EV1/EV2, ISO
- 14443 A/B, ISO 15693) read/write encoder
- Contact smart card encoder reads from and writes to all ISO7816 1/2/3/4 memory and microprocessor smart cards (T=0, T=1) as well as synchronous cards
- ISO magnetic stripe encoding, dual high- and low-coercivity, tracks 1, 2 and 3


## Specifications

<b>Print Method</b>	Dye sublimation / resin thermal transfer
<b>Resolution</b>	300 dpi (11.8 dots/mm) continuous tone
<b>Colours</b>	Up to 16.7 million / 256 shades per pixel

The DTC4500e is compatible with a variety of economical, eco-friendly refill ribbons for the reusable ECO cartridge:

<b>Print Ribbon Options</b>	<ul style="list-style-type: none"> <li>• Full-colour with resin black and overlay panel, YMCKO*, 500 prints</li> <li>• Full-colour half-panel with resin black and overlay panel, YMCKO*, 850 prints</li> <li>• Full-colour with two resin black panels and overlay panel, YMCKOK*, 500 prints</li> <li>• Full-colour with fluorescing, resin black and overlay panel, YMCFKO*, 500 prints</li> <li>• Full-colour with two resin black panels, YMCKK*, 500 prints</li> <li>• Resin black (standard and premium), 3000 prints</li> <li>• Resin white, 2000 prints</li> </ul>	
	<b>Print Speed</b>	6 seconds per card (K*); 8 seconds per card (KO*); 16 seconds per card (YMCKO*); 24 seconds per card (YMCKOK*)
	<b>Security Features</b>	Optional locking hoppers; password protection; AES 256 encryption; resin scramble data protection; fluorescent panel printing
	<b>Accepted Standard Card Sizes</b>	CR-80 (3.375" L x 2.125" W / 85.6 mm L x 54 mm W); CR-79 adhesive back (3.313" L x 2.063" W / 84.1 mm L x 52.4 mm W)
	<b>Print Area</b>	CR-80 edge-to-edge (3.36" L x 2.11" W / 85.3 mm L x 53.7 mm W); CR-79 (3.3" L x 2.04" W / 83.8 mm L x 51.8 mm W)
	<b>Accepted Card Thickness</b>	Print only: .009" - .040" / 9 mil - 40 mil / .229 mm - 1.016 mm; print / lamination: .030" - .040" / 30 mil - 40 mil / .762 mm - 1.02 mm
<b>Accepted Card Types</b>	PVC or polyester cards with polished PVC finish; monochrome resin required for 100% polyester cards; rewrite	
<b>Input Hopper Card Capacity</b>	100 cards per input hopper (.030" / .762 mm) - Dual input hopper standard on every unit for a total input capacity of 200 cards	
<b>Output Hopper Card Capacity</b>	Single-sided: Up to 30 cards. Dual-sided: Up to 100 cards. (.030" / .762 mm)	
<b>Card Cleaning</b>	Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon change	
<b>Memory</b>	32 MB RAM	
<b>Software Drivers</b>	Windows® 7 / 10 / 11 / Server 2012 / Server 2016 / Server 2019 / Server 2022	
<b>Interface</b>	USB 2.0, optional Ethernet with internal print server	
<b>Operating Temperature</b>	65° to 80° F / 18° to 27° C	
<b>Humidity</b>	20-80% non-condensing	
<b>Dimensions</b>	Single-sided printer: 9,8" H x 18,1" W x 9,2" D / 249 mm H x 460 mm W x 234 mm D	
	Dual-sided printer: 9,8" H x 18,7" W x 9,2" D / 249 mm H x 475 mm W x 234 mm D	
	Printer + laminator: 18,9" H x 18,7" W x 9,2" D / 480mm H x 475 mm W x 234 mm D	
<b>Weight</b>	Single-sided: 9 lbs. / 4,1 Kg; dual-sided: 11 lbs. / 5 Kg; printer + laminator: 20 lbs. / 9,1 kg	
<b>Agency Listings</b>	Safety: UL 60950-2, CSA C22.2 (60950-07), and CE; EMC: FCC Class A, CE (EN 55022 Class A, EN 55024), CCC, BSMI, KC	
<b>Environmental Features</b>	GreenCircle® Certified card printer (base models only without encoders), refillable supply cartridges (ECO), card rewrite support	
<b>Supply Voltage</b>	100-240Vac, 50-60Hz, 1,6 Amps max	
<b>Supply Frequency</b>	50 Hz / 60 Hz	
<b>Warranty</b>	Printer: three years**; printhead: three years**, unlimited card passes with UltraCard™	
<b>Encoding Options (HID Encoders)</b>	Supported smart card and magnetic stripe technologies: 125 kHz (HID Prox) reader; 13.56 MHz (iCLASS® Standard / SE / SR / Seos, MIFARE Classic®, MIFARE Plus®, MIFARE DESFire®, MIFARE DESFire EV1/EV2, ISO 14443 A/B, ISO 15693) read/write encoder; contact smart card encoder reads from and writes to all ISO7816 1/2/3/4 memory and microprocessor smart cards (T=0, T=1) as well as synchronous cards; ISO magnetic stripe encoding, dual high- and low-coercivity, tracks 1, 2 and 3	
<b>Options</b>	Dual-sided printing; single- or dual-sided lamination; same-side input/output card hopper; locking card input/output hopper; smart card encoding (contact/contactless); magnetic stripe encoding; printer cleaning kit; Ethernet with internal print server; secure proprietary consumables system	
<b>Display</b>	User-friendly, SmartScreen graphical display	

\* Indicates the ribbon type and the number of ribbon panels printed where Y=yellow, M=magenta, C=cyan, K=resin black, O=overlay, F=fluorescing  
 \*\*Three-year warranty available on printers and printheads with completion of online printer registration. (Two-year warranty standard on both printer and printheads without online printer registration.)



[www.infordata-shop.com](http://www.infordata-shop.com)  
sales@infordata.it - +39 040 367 189